

7-16 DIN ADAPTERS

7-16 DIN

PLATING SPECIFICATIONS

Body: S - Silver **Pin/Contact: S - Silver** **Dielectric: T - PTFE**
Interface Impedance: 50 Ω **Frequency Range: 0 TO 7.5 GHz** **PIM: ≥ - .150 dBc**




FIG. 1
RFD-1650-2



FIG. 2
RFD-1652-2



FIG. 3
RFD-1653-2



FIG. 4
RFD-1658-2



FIG. 5
RFD-1660-2



FIG. 6
RFD-1670-2



FIG. 7
RFD-1671-2



FIG. 8
RFD-1672-2



FIG. 9
RFD-1673-2

PHOTOS FOR REFERENCE ONLY, SHOWN AT 75% ACTUAL SIZE.

PART #	FIG	DESCRIPTION	NOTES	PLATING		
				BDY	P/C	DIE
RFD-1650-2	1	Barrel Adapter	7-16 DIN Male to 7-16 DIN Male	S	S	T
RFD-1652-2	2	Right Angle Adapter	7-16 DIN Male to 7-16 DIN Female	S	S	T
RFD-1653-2	3	Barrel Adapter	7-16 DIN Female to 7-16 DIN Female	S	S	T
RFD-1658-2	4	Right Angle Adapter	7-16 DIN Female to 7-16 DIN Female	S	S	T
RFD-1660-2	5	Barrel Adapter	7-16 DIN Female to 7-16 DIN Male	S	S	T
RFD-1670-2	6	Adapter	7-16 DIN Male to N Male	S	S	T
RFD-1671-2	7	Adapter	7-16 DIN Male to N Female	S	S	T
RFD-1672-2	8	Adapter	7-16 DIN Female to N Male	S	S	T
RFD-1673-2	9	Adapter	7-16 DIN Female to N Female	S	S	T

