

SPECIFICATIONS		CABLE GROUPS	
ELECTRICAL SPECIFICATIONS IMPEDANCE: NON-CONSTANT WORKING VOLTAGE RATING: 1,600 VRMS (MATED PAIR) FREQUENCY RANGE: N/A MECHANICAL SPECIFICATIONS MATING: 2-STUD BAYONET COUPLING INTERFACE: MIL-STD-348, SECTION 303 CABLING: CLAMP, CRIMP AND SOLDER PLATING G - GOLD N - NICKEL DIELECTRIC MATERIAL T - PTFE	GRP	FOR THESE CABLE TYPES	
	D	RG-59, 59A, 59B, 62, 62A, 62C/U; ALPHA 9059, 9062, 9830, 9840, 9845; BELDEN 8221, 8241, 9169, 9204, 9228; CANARE LV-61S; COMMSCOPE 5550, 5555, 5560, 5563	
	E	TIMES AA-4478; RG-8, 8A, 213/U; ALPHA 9008, 9213; BELDEN 8267, 9251, 9880, 89880; INTERCOMP 4082, 22132	
	X	TIMES LMR-240, LMR-240 ULTRAFLEX; RG-8X; ANDREW CNT-240, CNT-240AL, CNT-240ALS, CNT-240-DB, CNT-240-FR, CNT-240-W; BELDEN 9258; COMMSCOPE TCOM-240, TCOM-240-FR, WBC-240, WBC-240R; HARBOUR HPF240; MICRO 8/U; REMEE 1600; SAXTON 8315	
FOR A MORE EXTENSIVE LISTS OF CABLE GROUPS			



FIG. 1
RHV-100-D



FIG. 2
RHV-100-E



FIG. 3
RHV-106-D, -X



FIG. 4
RHV-116



FIG. 5
RHV-124-D




FIG. 6
RHV-130



FIG. 7
RHV-134

PHOTOS FOR REFERENCE ONLY, SHOWN AT 100% ACTUAL SIZE.

[FOR MOUNTING CONFIGURATIONS](#)

PART #	FIG	DESCRIPTION	CBL GRP	NOTES	PLATING			RECOMMENDED TOOL
					BDY	P/C	DIE	
RHV-100-D	1	High Voltage Male Clamp	D	for RG-59/U	N	G	T	RFA-4009-206
RHV-100-E	2	High Voltage Male Clamp	E	for RG-213/U	N	G	T	RFA-4009-205
RHV-106-D	3	High Voltage Male Crimp	D	for RG-59/U (22-23 AWG only)	N	G	T	RFA-4009-203
RHV-106-X	3	High Voltage Male Crimp	X	for LMR-240	N	G	T	RFA-4009-203
RHV-116	4	High Voltage Female Bulkhead		Front Mount with D Flat and O Ring	N	G	T	
RHV-124-D	5	Female Clamp	D	for RG-59/U	N	G	T	RFA-4009-206
RHV-130	6	Female, Male, Female, T Adapter			N	G	T	
RHV-134	7	MHV Female to MHV Female Adapter			N	G	T	