



SPECIFICATIONS	CABLE GROUPS	
ELECTRICAL SPECIFICATIONS IMPEDANCE: 50 Ω WORKING VOLTAGE RATING: 170 VRMS FREQUENCY RANGE: 0-6 GHZ MECHANICAL SPECIFICATIONS MATING: SNAP ON COUPLING INTERFACE: CECC 22000 CABLING: CRIMP AND PCB SOLDERING PLATING G - GOLD DIELECTRIC MATERIAL T - PTFE	GRP	FOR THESE CABLE TYPES
	A	RG-178, 178A, 178B, 196, 196A/U; BELDEN 83265
	B	TIMES LMR-100A; RG-174, 188, 188A, 316/U; ALPHA 9174, 9316; BELDEN 7805A, 8216, 83269, 83284, 84316; COMMSCOPE AMC-174, WBC-100
	B1	RG-316/U DOUBLE SHIELD; RD-316; BELDEN 83269; COLEMAN 1596
FOR A MORE EXTENSIVE LISTING OF CABLE GROUPS		



PHOTOS FOR REFERENCE ONLY, SHOWN AT 250% ACTUAL SIZE.

FOR MOUNTING CONFIGURATIONS

PART #	FIG	DESCRIPTION	CBL GRP	NOTES	PLATING			RECOMMENDED TOOL
					BDY	P/C	DIE	
RMX-9000-1A	1	Crimp Plug	A	for RG-178/U	G	G	T	RFA-4009-204
RMX-9000-1B	1	Crimp Plug	B, B1	for RG-174/U, RG-316/U RG-316/U Double Shield	G	G	T	RFA-4009-204
RMX-9000-1B1	1	Crimp Plug	B, B1	for RG-174/U, RG-316/U & RG-316/U Double Shield	G	G	T	RFA-4009-204
RMX-9010-1A	2	Right Angle Crimp Plug	A	for RG-178/U	G	G	T	RFA-4009-204
RMX-9010-1B	2	Right Angle Crimp Plug	B	for RG-174/U & RG-316/U	G	G	T	RFA-4009-204
RMX-9010-1B1	2	Right Angle Crimp Plug	B1	for RG-174 Double Shield & RG-316/U Double Shield	G	G	T	RFA-4009-204
RMX-9050-1B	3	Crimp Jack	B	for RG-174/U & RG-316/U	G	G	T	RFA-4009-204
RMX-9050-1B1	3	Crimp Jack	B1	for RG-316/U Double Shield	G	G	T	RFA-4009-204
RMX-9060-1B	4	Right Angle Crimp Jack	B	for RG-174/U & RG-316/U	G	G	T	RFA-4009-204
RMX-9060-1B1	4	Right Angle Crimp Jack	B1	for RG-316/U Double Shield	G	G	T	RFA-4009-204
RMX-9350-1	5	Vertical PCB Jack			G	G	T	