

7-16 DIN Adapters

PLATING SPECIFICATIONS

BODY: S - SILVER **PIN/CONTACT:** S - SILVER **DIELECTRIC PLATING:** T - TEFLON
INTERFACE **IMPEDANCE:** 50 Ω **FREQUENCY RANGE:** 0 TO 7.5 GHz **PIM:** ≥ -.150 dBc

7-16 DIN



FIG. 1
RFD-1650-2



FIG. 2
RFD-1652-2



FIG. 3
RFD-1653-2



FIG. 4
RFD-1658-2



FIG. 5
RFD-1660-2



FIG. 6
RFD-1670-2



FIG. 7
RFD-1671-2



FIG. 8
RFD-1672-2



FIG. 9
RFD-1673-2

PHOTOS FOR REFERENCE ONLY, SHOWN AT 75% ACTUAL SIZE.

PART #	FIG	DESCRIPTION	NOTES	PLATING		
				BDY	P/C	DIE
RFD-1650-2	1	BARREL ADAPTER	7-16 DIN MALE TO 7-16 DIN MALE	S	S	T
RFD-1652-2	2	RIGHT ANGLE ADAPTER	7-16 DIN MALE TO 7-16 DIN FEMALE	S	S	T
RFD-1653-2	3	BARREL ADAPTER	7-16 DIN FEMALE TO 7-16 DIN FEMALE	S	S	T
RFD-1658-2	4	RIGHT ANGLE ADAPTER	7-16 DIN FEMALE TO 7-16 DIN FEMALE	S	S	T
RFD-1660-2	5	BARREL ADAPTER	7-16 DIN FEMALE TO 7-16 DIN MALE	S	S	T
RFD-1670-2	6	ADAPTER	7-16 DIN Male to N Male	S	S	T
RFD-1671-2	7	ADAPTER	7-16 DIN Male to N Female	S	S	T
RFD-1672-2	8	ADAPTER	7-16 DIN Female to N Male	S	S	T
RFD-1673-2	9	ADAPTER	7-16 DIN Female to N Female	S	S	T