

MALE		FEMALE																																						
	<table border="1"> <thead> <tr> <th rowspan="2">LETTER</th> <th colspan="2">INCHES [MILLIMETERS]</th> </tr> <tr> <th>MINIMUM</th> <th>MAXIMUM</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>.1783 [4.53]</td> <td>.1807 [4.59]</td> </tr> <tr> <td>B</td> <td>.1374 [3.49]</td> <td>.1383 [3.51]</td> </tr> <tr> <td>C</td> <td>.0354 [0.90]</td> <td>.0366 [0.93]</td> </tr> <tr> <td>D</td> <td>.060 [1.52]</td> <td>.070 [1.78]</td> </tr> <tr> <td>E</td> <td>.092 [2.34]</td> <td>.096 [2.44]</td> </tr> </tbody> </table>	LETTER	INCHES [MILLIMETERS]		MINIMUM	MAXIMUM	A	.1783 [4.53]	.1807 [4.59]	B	.1374 [3.49]	.1383 [3.51]	C	.0354 [0.90]	.0366 [0.93]	D	.060 [1.52]	.070 [1.78]	E	.092 [2.34]	.096 [2.44]		<table border="1"> <thead> <tr> <th rowspan="2">LETTER</th> <th colspan="2">INCHES [MILLIMETERS]</th> </tr> <tr> <th>MINIMUM</th> <th>MAXIMUM</th> </tr> </thead> <tbody> <tr> <td>F</td> <td>.208 [5.28]</td> <td>.212 [5.38]</td> </tr> <tr> <td>G</td> <td>.181 [4.60]</td> <td>.183 [4.65]</td> </tr> <tr> <td>H</td> <td>.1374 [3.49]</td> <td>.1382 [3.51]</td> </tr> <tr> <td>I</td> <td>.075 [1.91]</td> <td>.077 [1.96]</td> </tr> </tbody> </table>	LETTER	INCHES [MILLIMETERS]		MINIMUM	MAXIMUM	F	.208 [5.28]	.212 [5.38]	G	.181 [4.60]	.183 [4.65]	H	.1374 [3.49]	.1382 [3.51]	I	.075 [1.91]	.077 [1.96]
LETTER	INCHES [MILLIMETERS]																																							
	MINIMUM	MAXIMUM																																						
A	.1783 [4.53]	.1807 [4.59]																																						
B	.1374 [3.49]	.1383 [3.51]																																						
C	.0354 [0.90]	.0366 [0.93]																																						
D	.060 [1.52]	.070 [1.78]																																						
E	.092 [2.34]	.096 [2.44]																																						
LETTER	INCHES [MILLIMETERS]																																							
	MINIMUM	MAXIMUM																																						
F	.208 [5.28]	.212 [5.38]																																						
G	.181 [4.60]	.183 [4.65]																																						
H	.1374 [3.49]	.1382 [3.51]																																						
I	.075 [1.91]	.077 [1.96]																																						
SPECIFICATIONS																																								
<b>PLATING</b> G - GOLD SS - STAINLESS STEEL  <b>DIELECTRIC</b> R - REXOLITE	<b>GENERAL SPECIFICATIONS</b> MATERIALS: BODY: STAINLESS STEEL, CORROSION-RESISTANT, NON-MAGNETIC 303, PER ASTM A484 AND A582. CONTACTS: BERYLLIUM COPPER, QQ-C 530, ALLOY 173. DIELECTRIC: REXOLITE® FINISH: CENTER CONTACTS ARE GOLD PLATED PER MIL-G- 45204 TYPE II, CLASS 1 OVER NICKEL PLATE PER QQ-N-290. BODY AND BODY COMPONENTS ARE PASSIVATED PER ASTM A380.	<b>ELECTRICAL SPECIFICATIONS</b> NOMINAL IMPEDANCE: 50 Ω FREQUENCY: DC-34 GHZ VSWR: 1.05 + .006 F (F=GHZ) MAX. DC-34 GHZ CONTACT RESISTANCE: CENTER CONTACT = 3.0 MILLIOHMS, OUTER CONTACT = 2.0 MILLIOHMS	<b>ENVIRONMENTAL SPECIFICATIONS</b> TEMPERATURE RATING: -55° C TO +105° C																																					
	<b>MECHANICAL SPECIFICATIONS</b> CONNECTOR DURABILITY: 500 CYCLES MINIMUM CONTACT TORQUE: 4.0 INCH-OUNCES MINIMUM COUPLING NUT MATING TORQUE: 8-10 LBS																																							



FIG. 1  
RF35F-35F-00000



FIG. 2  
RF35M-35F-00000



FIG. 3  
RF35M-35M-00000, -G0000

PHOTOS FOR REFERENCE ONLY, SHOWN AT 150% ACTUAL SIZE.

PART #	FIG	DESCRIPTION	NOTES	PLATING		
				BDY	P/C	DIE
RF35F-35F-00000	1	ADAPTER	3.5mm Female to 3.5mm Female	SS	G	R
RF35M-35F-00000	2	ADAPTER	3.5mm Male to 3.5mm Female	SS	G	R
RF35M-35M-00000	3	BULKHEAD ADAPTER	3.5mm Male to 3.5mm Male	SS	G	R
RF35M-35M-G0000	3	ADAPTER	3.5mm Male to 3.5mm Male	G	G	R



RFA-4031-01