

2.9mm

2.9mm



PLUG		JACK																																									
	<table border="1"> <thead> <tr> <th rowspan="2">LETTER</th> <th colspan="2">INCHES [MILLIMETERS]</th> </tr> <tr> <th>MINIMUM</th> <th>MAXIMUM</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>.1783 [4.53]</td> <td>.1807 [4.59]</td> </tr> <tr> <td>B</td> <td>.1147 [2.91]</td> <td>.1154 [2.93]</td> </tr> <tr> <td>C</td> <td>.0354 [0.90]</td> <td>.0366 [0.93]</td> </tr> <tr> <td>D</td> <td>.060 [1.52]</td> <td>.070 [1.78]</td> </tr> <tr> <td>E</td> <td>.092 [2.34]</td> <td>.096 [2.44]</td> </tr> </tbody> </table>	LETTER	INCHES [MILLIMETERS]		MINIMUM	MAXIMUM	A	.1783 [4.53]	.1807 [4.59]	B	.1147 [2.91]	.1154 [2.93]	C	.0354 [0.90]	.0366 [0.93]	D	.060 [1.52]	.070 [1.78]	E	.092 [2.34]	.096 [2.44]		<table border="1"> <thead> <tr> <th rowspan="2">LETTER</th> <th colspan="2">INCHES [MILLIMETERS]</th> </tr> <tr> <th>MINIMUM</th> <th>MAXIMUM</th> </tr> </thead> <tbody> <tr> <td>F</td> <td>.208 [5.28]</td> <td>.212 [5.38]</td> </tr> <tr> <td>G</td> <td>.181 [4.60]</td> <td>.183 [4.65]</td> </tr> <tr> <td>H</td> <td>.1146 [2.91]</td> <td>.1154 [2.93]</td> </tr> <tr> <td>I</td> <td>.0496 [1.26]</td> <td>.0504 [1.28]</td> </tr> <tr> <td>J</td> <td>.075 [1.91]</td> <td>.077 [1.96]</td> </tr> </tbody> </table>	LETTER	INCHES [MILLIMETERS]		MINIMUM	MAXIMUM	F	.208 [5.28]	.212 [5.38]	G	.181 [4.60]	.183 [4.65]	H	.1146 [2.91]	.1154 [2.93]	I	.0496 [1.26]	.0504 [1.28]	J	.075 [1.91]	.077 [1.96]
LETTER	INCHES [MILLIMETERS]																																										
	MINIMUM	MAXIMUM																																									
A	.1783 [4.53]	.1807 [4.59]																																									
B	.1147 [2.91]	.1154 [2.93]																																									
C	.0354 [0.90]	.0366 [0.93]																																									
D	.060 [1.52]	.070 [1.78]																																									
E	.092 [2.34]	.096 [2.44]																																									
LETTER	INCHES [MILLIMETERS]																																										
	MINIMUM	MAXIMUM																																									
F	.208 [5.28]	.212 [5.38]																																									
G	.181 [4.60]	.183 [4.65]																																									
H	.1146 [2.91]	.1154 [2.93]																																									
I	.0496 [1.26]	.0504 [1.28]																																									
J	.075 [1.91]	.077 [1.96]																																									
SPECIFICATIONS		CABLE GROUPS																																									
ELECTRICAL SPECIFICATIONS IMPEDANCE: 50 Ω WORKING VOLTAGE RATING: 250 VRMS FREQUENCY RANGE: 0-40 GHz MECHANICAL SPECIFICATIONS MATING: .250 - 36 THREAD DURABILITY: 500 CYCLES MINIMUM CABLING: SOLDER PLATING G - GOLD DIELECTRIC MATERIAL T - TEFLON		GRP FOR THESE CABLE TYPES SR1 .085 SEMI RIGID; RG-405/U; BELDEN 1671A; RD-179																																									



FIG. 1
RF29M-SR1

PHOTOS FOR REFERENCE ONLY, SHOWN AT 200% ACTUAL SIZE.

PART #	FIG	DESCRIPTION	CBL GRP	NOTES	PLATING		
					BDY	P/C	DIE
RF29M-SR1	1	PLUG	SR1	DIRECT SOLDER	G	G	T