

SPECIFICATIONS	CABLE GROUPS	
ELECTRICAL SPECIFICATIONS IMPEDANCE: 75 Ω WORKING VOLTAGE RATING: N/A MECHANICAL SPECIFICATIONS MATING: PUSH-ON PLATING G - GOLD N - NICKEL DIELECTRIC MATERIAL D - DELRIN PP - POLYPROPYLENE	GRP	FOR THESE CABLE TYPES
	D	RG-59, 59A, 59B, 62, 62A, 62C/U; ALPHA 9059, 9062, 9830, 9840, 9845; BELDEN 8221, 8241, 9169, 9204, 9228; CANARE LV-61S; COMMSCOPE 5550, 5555, 5560, 5563



FIG. 1
RCA-1902




FIG. 2
RCA-1903



FIG. 3
RCA-1904-01-D,
-02-D, -03-D



FIG. 4
RCA-1950-03

PHOTOS FOR REFERENCE ONLY, SHOWN AT 100% ACTUAL SIZE.

PART #	FIG	DESCRIPTION	CBL GRP	NOTES	PLATING			RECOM- MENDED TOOL
					BDY	P/C	DIE	
RCA-1902	1	MALE CRIMP	D	FOR RG-59/U	N	N	PP	RFA-4009-203
RCA-1903	2	MALE SOLDER	D	INTREGRAL SPRING STRAIN RELIEF: FOR RG-59/U	G	G	PP	
RCA-1904-01-D	3	MALE COMPRESSION CRIMP	D	RED RING: FOR RG-59/U	N	N	PP	RFA-4004-20
RCA-1904-02-D	3	MALE COMPRESSION CRIMP	D	WHITE RING: FOR RG-59/U	N	N	PP	RFA-4004-20
RCA-1904-03-D	3	MALE COMPRESSION CRIMP	D	YELLOW RING: FOR RG-59/U	N	N	PP	RFA-4004-20
RCA-1950-03	4	RCA JACK TO RCA JACK BULKHEAD ADAPTER		WITH D-FLAT	N	G	D	