



P2RFD-1673-4

Description: 7-16 DIN adapters are highly desired in test applications such as base station PIM testing. These low loss, low VSWR adapters are designed to be used with portable antenna and cable analyzers. Anritsu's Site Master™, Summitek's SI™ series and Boonton's PIM testers are examples where high grade DIN adapters are used. Some features to highlight are White Bronze plated bodies for tarnish free service and superior electrical performance along with low passive intermodulation products. (PIM) White Bronze plating offers a non-magnetic solution while retaining high conductivity and low resistivity in the conductor paths. Engineered for long life in field applications, they are also suitable for lab environments. All 7-16 DIN adapters are machined to exacting specifications and stand up to the competition surpassing expectation when compared to typical Silver plated products. Test charts included.

Electrical: Frequency range.....DC to 8.0 GHz
 Velocity of Propagation 77%
 Impedance50 ± 1 ohm
 Delay..... 132 ps over 8.0 GHz span
 VSWR..... <1.2:1 to 8.0 GHz
 Insertion Loss..... <-.1 dB to 8.0 GHz
 3rd Order IMP >-170dBc in PCS band w/2 +43 dB tones

Mechanical: Mating..... M29 X 1.5mm; 5/8-24UNEF Thread
 Interface..... MIL-STD-348; CECC 22 190
 Mating cycles 500 min

Materials and finish:
 Body, Ground rings Brass, BeCu, White Bronze
 Insulator PTFE
 Contacts.....BeCu; W.B. over Silver over Copper

VSWR Chart:

