

BNC 75 OHM ADAPTERS

PLATING SPECIFICATIONS

BODY: N - NICKEL S - SILVER **PIN/CONTACT:** G - GOLD S - SILVER **DIELECTRIC:** D - DELRIN T - TEFLON



FIG. 1
RFB-1730



FIG. 2
RFB-1730-3, -4



FIG. 3
RFB-1732



FIG. 4
RFB-1733



FIG. 5
RFB-1734, -2



FIG. 6
RFB-1735, -1



FIG. 7
RFB-1745

PHOTOS FOR REFERENCE ONLY, SHOWN AT 100% ACTUAL SIZE

PART #	FIG	DESCRIPTION	NOTES	REPLACES OR EQUIVALENT TO	PLATING		
					BDY	P/C	DIE
RFB-1730	1	T ADAPTER	BNC MALE TO DOUBLE BNC FEMALE	AMPHENOL 31-70036	N	G	T
RFB-1730-3	2	F ADAPTER	BNC MALE TO DOUBLE BNC FEMALE		N	G	T
RFB-1730-4	2	F ADAPTER	BNC MALE TO DOUBLE BNC FEMALE W/ INTERNAL 75 OHM RESISTORS (VIDEO SPLITTER)		N	G	D
RFB-1732	3	RIGHT ANGLE ADAPTER	BNC MALE TO BNC FEMALE	AMPHENOL 31-9-75	N	G	T
RFB-1733	4	BARREL ADAPTER	BNC MALE TO BNC MALE	AMPHENOL 31-218-75	N	G	T
RFB-1734	5	BARREL ADAPTER	BNC FEMALE TO BNC FEMALE	AMPHENOL 31-219-75	N	G	T
RFB-1734-2	5	BARREL ADAPTER	BNC FEMALE TO BNC FEMALE		S	G	T
RFB-1735	6	FEMALE BULKHEAD ADAPTER	DOUBLE BNC FEMALE WITH D-FLAT & O-RING	AMPHENOL 31-70020	N	G	T
RFB-1735-1	6	FEMALE BULKHEAD ADAPTER	DOUBLE BNC FEMALE WITH D-FLAT, INSULATED	AMPHENOL 31-4803-75	N	G	T
RFB-1745	7	STRAIGHT ADAPTER	BNC FEMALE TO 1/4X24 STUD, FOR KENWOOD TK240, TK340	MIDLAND 70-1034	N	S	T

BNC - 75 Ohm

BNC - 75 Ohm