


SPECIFICATIONS

<p>ELECTRICAL SPECIFICATIONS</p> <p>IMPEDANCE: 75 Ω</p> <p>WORKING VOLTAGE RATING: 335 VRMS @ SEA LEVEL (DEPENDENT ON CABLE)</p> <p>FREQUENCY RANGE: 0-4 GHZ</p>	<p>MECHANICAL SPECIFICATIONS</p> <p>MATING: SNAP LOCK</p> <p>INTERFACE: MIL-STD-348</p> <p>CABLING: CRIMP, PCB SOLDER</p>	<p>PLATING</p> <p>G - GOLD</p>	<p>DIELECTRIC MATERIAL</p> <p>T - TEFLON</p>
---	--	---------------------------------------	---



PHOTOS FOR REFERENCE ONLY, SHOWN AT 150% ACTUAL SIZE.

FOR MOUNTING CONFIGURATIONS REFER TO PAGES 149-164

PART #	FIG	DESCRIPTION	CABLE GROUPS	PLATING			RECOMMENDED TOOL
				BDY	P/C	DIE	
RSB-200-1-179	1	CRIMP PLUG	FOR RG-179/U ONLY	G	G	T	RFA-4009-204
RSB-200-1S1	1	CRIMP PLUG	FOR RG-179/U DOUBLE SHIELD	G	G	T	RFA-4009-204
RSB-210-1-179	2	RIGHT ANGLE CRIMP PLUG	FOR RG-179/U ONLY	G	G	T	RFA-4009-204
RSB-210-1-S1	2	RIGHT ANGLE CRIMP PLUG	FOR RG-179/U DOUBLE SHIELD	G	G	T	RFA-4009-204
RSB-220-1-179	3	CRIMP JACK	FOR RG-179/U ONLY	G	G	T	RFA-4009-204
RSB-221-1-179	4	BULKHEAD CRIMP JACK	FOR RG-179/U ONLY	G	G	T	RFA-4009-204
RSB-250-1	5	VERTICAL JACK PCB MOUNT		G	G	T	
RSB-255-1	6	RIGHT ANGLE JACK PCB MOUNT		G	G	T	
RSB-260-1	7	VERTICAL PLUG PCB MOUNT		G	G	T	
RSB-265-1	8	RIGHT ANGLE PLUG PCB MOUNT		G	G	T	