



DELUXE CRIMPING TOOL AND DIE KIT (RFA-4006-500)

- Our most complete crimp kit
- 2 crimp handles **RFA-4005-20**
- 17 changeable die sets
- Crimp coax cable terminals
- From RG-174/U to LMR-400 (AWG 8-22)
- Rugged, foam-lined case

EXPANDABLE CRIMPING TOOL AND DIE KITS

- Crimper(s) housed in durable, padded self-storage case
- Room for additional dies of your choice








COAX HEX DIES FOR RFA-4005-20 CRIMPER



Buy separately or with tool

Specific Die	Part Number for Die with Crimp Tool in Cardboard Box
RFA-4005-01	RFA-4005-400
RFA-4005-02	RFA-4005-300
RFA-4005-04	RFA-4005-304
RFA-4005-05	RFA-4005-305
RFA-4005-06	RFA-4005-306
RFA-4005-07	RFA-4005-307
RFA-4005-08	RFA-4005-308
RFA-4005-09	RFA-4005-309
RFA-4005-10	RFA-4005-310
RFA-4005-14	RFA-4005-314



All dies are available separately

COMMERCIAL GRADE MODULAR DIES		
	Description	Part Number
	For non-insulated terminals AWG 22-8	RFA-4005-21
	For non-insulated flag terminals from 0.5 to 2.5 sq.mm. AWG 22-18, 16-14	RFA-4005-22
	For cord end terminals from 0.5 to 10 sq.mm. AWG 22-8	RFA-4005-23
	For insulated terminals from 0.5 to 6 sq.mm. AWG 22-18, 16-14, 12-10	RFA-4005-24
	For non-insulated open barrel terminal from 0.5 to 6 sq.mm. AWG 22-18, 16-14, 12-10	RFA-4005-25
	For non-insulated terminals and cable lugs from 1.5 to 6 sq.mm. AWG 22-18, 16-14, 12-10	RFA-4005-26
	For non-insulated terminals DIN 46234 from 0.5 to 10 sq.mm. AWG 22-18, 16-14, 12-10, & 8	RFA-4005-27

COMMERCIAL GRADE COAXIAL DIES		
	RG-58/U, RG-59/U, RG-142/U, RG-223/U, RG-400/U, RG-8X, PROFLEX AND VARIOUS VIDEO CABLES, CAVITY DIMENSIONS: .052", .068", .100", .213" AND .255".	RFA-4005-01
	RG-8/U, RG-213/U, RG-214/U, AND BELDEN 9913 CABLES, CAVITY DIMENSIONS: .100", .128" & .429". THE .128" CAVITY CRIMPS THE CENTER PIN ON BELDEN 9913 CABLE.	RFA-4005-02
	228", .068", .305", for RG-58/U, RG-59/U, RG-62/U and Cambridge Connectors Series CP-88 & CP-89	RFA-4005-04
	155", .184", .215"	RFA-4005-05
	255", .324", .354" for RG-59/U, RG-6/U, and F-Type (CATV) Coax Connectors	RFA-4005-06
	213", .178", .068", .042", for RG-58/U, RG-174/U, RG-316/U Coax Connectors (RFI Cable Groups B and C)	RFA-4005-07
	324", .255", .068", .042", for RG-59/U and Belden 8281 Coax Cable (RFI Cable Groups D and G)	RFA-4005-08
	.178", .128", .068", for RG-174/U, RG-188/U, RG-316/U and Mini 59/U Coax Connectors (RFI Cable Group B)	RFA-4005-09
	080", .100", .429" for RG-8/U, RG-11/U and RG-213/U (RFI Cable Group E)	RFA-4005-10
	Belden 9913, LMR®-400, WBC-400 (RFI Cable Group I); .429", .118" hex cavities	RFA-4005-14